

Landscape Transformers



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- LARGE SECONDARY CONNECTION BLOCK FOR EASY WIRING
- 1/8" STAINLESS STEEL NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- COMES STANDARD WITH 6 FOOT PRIMARY LINE CORD
- MULTI-VOLT SECONDARY UP TO 15 VOLTS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.
- TIMER AND PHOTOCELL READY. SOLD SEPARATELY.

REQUIREMENTS

- MEETS OR EXCEEDS THE UL STANDARD 1838 FOR LANDSCAPE LIGHTING
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME

	150 WATT	300 WATT
PART NUMBER	1023-12-SS	1101-12-SS
PRIMARY VOLTAGE	120VAC-1A MAX	120VAC-3A MAX
OUTPUT VOLTAGE	12, 13, 14, 15 VAC	12, 13, 14, 15 VAC
BREAKERS	1x15A	1x25A
FREQUENCY	60 Hz	60 Hz
DIMENSIONS	15-1/4" x 4-3/4" x 5-1/2"	17" x 7-1/2" x 5-1/2"
WEIGHT	15 LBS.	20 LBS.