


# MODUX TWO HANGING LIGHT

## Specifications

<b>LED</b>	Screw Mounted 2W 3Vf Cree XPG-3 LED
<b>Power</b>	2 Watt
<b>Output*</b>	175lm, 89 lm/w
<b>LED Life Expectancy</b>	50,000 hours L70
<b>CRI (3000K)</b>	90+
<b>Ingress Protection</b>	IP68
<b>Warranty</b>	Electronics = 5 years (Excludes third party lamps and power supplies) Aluminium = 5 years Brass = 10 years Stainless Steel = 10 years



### Standards

\*Delivered from the luminaire with an unobstructed beam

## Product Configuration

○ M2HL

Power	Material/Finish	Beam	Colour	Accessories
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
<p><b>R</b> Constant Current Input, Series Wired, 2W Requires Constant Current Driver (not supplied). Fixture Input: 3Vf @ 700mA maximum.</p> <p><b>IA</b> 12VAC Input, Parallel Wired, 2W Requires Magnetic/Wire Wound 12VAC Transformer (not supplied). Fixture Input: 12VAC, 2W (700mA).</p> <p><b>ID</b> 24VDC Input, Parallel Wired, 2W Requires 24VDC Constant Voltage Power Supply (not supplied). Fixture Input: 24VDC, 2W (700mA).</p>	<p>Powder Coated Aluminium</p> <p><b>A</b></p> <ul style="list-style-type: none"> <li><b>EBK</b> Black</li> <li><b>EBZ</b> Bronze</li> <li><b>EOGR</b> Olive green</li> <li><b>EWH</b> White</li> <li><b>EWB</b> White Birch</li> <li><b>EDG</b> Dark Grey</li> <li><b>ESTAR</b> Silver Star</li> <li><b>ECT</b> Corten</li> <li><b>FS</b> Fine Silver</li> </ul> <p>Solid Metal Options</p> <ul style="list-style-type: none"> <li><b>B</b> Solid Brass</li> <li><b>AB</b> Aged Solid Brass</li> <li><b>S</b> 316 Stainless Steel</li> <li><b>EPS</b> Electropolished 316 Stainless Steel</li> </ul>	<ul style="list-style-type: none"> <li><b>26</b> 26 Degrees</li> <li><b>36</b> 36 Degrees</li> <li><b>74</b> 74 Degrees</li> </ul>	<ul style="list-style-type: none"> <li><b>2</b> 2700K</li> <li><b>3</b> 3000K</li> <li><b>4</b> 4000K</li> <li><b>A</b> Amber</li> <li><b>B</b> Blue</li> <li><b>G</b> Green</li> <li><b>R</b> Red</li> </ul>	<ul style="list-style-type: none"> <li><b>F</b> Frosted Lens</li> <li><b>H</b> Hex Cell Louvre</li> <li><b>GG</b> Glare Guard</li> <li><b>SNT</b> Snoot</li> </ul>

# Luminaire Information

CNC machined from the following materials

## Powder Coated Aluminium

Virgin, high corrosion resistant, low copper content (0.001%) aluminium with chromate substrate, and a highly UV-resistant polyester powder coat.

## Solid Brass

Virgin C38500 brass alloy made from copper, zinc, and lead with a warm gold-en colour. Naturally patinas over time to form a protective layer that improves corrosion resistance and durability.

## 316 Stainless Steel

316 Stainless Steel with high corrosion resistance and superior resistance against rust and abrasion.

## Gaskets

Silicone, iron impregnated 220°C (428°F).

## Lens

Extra clear, low iron, shatter resistant.

## Mounting

Hung via the provided stainless steel 3m hanging wire.

# Accessories



Frosted Lens



Hex Cell Louvre




Glare Guard




Snoot

# Beam Angle


Beam angles shown are based on 3000K. For other colours and full photometric data, IES files are available for download from our website.



26°



36°




74°

# Wiring Guide

Diagrams are a guide only, wire colours and polarity may change depending on fixture and country.


## Circuit: Wire in Series With Remote Driver

Please see installation instructions for full details.



## Circuit: 12VAC - Wire in Parallel

Please see installation instructions for full details.



## Circuit: 24VDC - Wired In Parallel

Please see installation instructions for full details.

